

# Steaming Hot/Cold System

No more noisy kettles! InSinkErator® all new steaming hot water taps deliver near-boiling water right at your kitchen sink. At the touch of a lever, they combine style with convenience.

H3300 (Hot only)  
HC3300 (Hot & Cold)

HC1100 (Hot & Cold)

GN1100 (Hot only)



**STEAMING HOT  
COLD FILTERED**



## FEATURES

- Modern contemporary design
- As the heated water is used, tap water enters the tank for quick heating. A fast recovery system can supply approximately 100 cups of near-boiling hot water per hour. Cup volume is 236ml. Yet each dispenser uses less energy than a 40-watt light bulb.
- Dispenses 98°C hot and ambient cold filtered water (HC3300 and GN1100 hot water only)
- Adjustable temperature dial
- Compact and convenient
- Unique single handle with a hot push-lever locking mechanism (H3300 and HC3300)
- 5 Micron Taste/Odour/Scale reduction filter included
- 2 year warranty

## DISCOVER THE CONVENIENCE!

### Food and drink

- Make tea, coffee and other hot drinks
- Prepare pasta and rice
- Blanche vegetables
- Create gravies, sauces and soups
- Thaw frozen food and warm ice cream scoops
- Re-hydrate dried food
- Clean fruit and vegetables

### Practical uses

- Washing up
- Remove lids from jars
- Clean wax from candle holders
- Remove labels from containers for recycling
- Add extra shine to silver
- Fill hot water bottles

### Baby care

- Warm bottle and food
- Clean without harsh chemicals

## SPECIFICATIONS

Tap	HC3300	H3300	HC1100	GN1100
Capacity	2.5 Litre Stainless Steel tank dispenses approximately 100 cups of 98°C water per hour. Cup volume is 236ml			
Electrical	220–240 volts A.C. 1300 watts, heating element with grounded plug. Requires 10 amps of power			
Thermostat	Electronic, adjustable from 88°C to 8°C (factory pre-set at 96°C)			
Insulation	Meets U.L. 94HF – 1 flammability specification			
Hot Valve	Push hot side activation with automatic shut off not (OptiPust)		Instant self closing	
Cold Valve	Manual return	N/A	Manual return	N/A
Weight	Approximately 4.4kg			
Required Hole Diameter	35mm–38mm	35mm–38mm	35mm–38mm	32mm–38mm
Required Supply Pressure	172–862 kPa (1.7–8.6 bar) (25–125 psi)			



Nationwide Sales & Service  
Freephone 0800 650 100  
Visit us at [www.aquafilter.co.nz](http://www.aquafilter.co.nz)

Head Office:  
Phone 09 414 5600 Fax 09 414 5601  
PO Box 300419, Albany, Auckland 0752  
Aqua Filter is a Member of the Aqua Synergy Group

